

SLIM-PIR-LUNA

SLIM-PIR-LUNA detects motion in the protected area. Additionally, the detector has a set of LEDs to implement the lighting feature.

- certificate of compliance with the EN 50131 requirements for Grade 2
- motion detection using passive infrared (PIR) sensor
- adjustable sensitivity of detection
- digital motion detection algorithm
- digital temperature compensation
- option to enable/disable the creep zone protection
- wide-angle lens, designed specifically for **SLIM LINE** detectors
- option to replace the wide-angle lens with the curtain (**CT-CL2**) or long-range (**LR-CL2**) one
- ability to configure detector operating parameters using the **OPT-1** keyfob
- built-in end-of-line resistors (2EOL: 2 x 1,1 k Ω / 2 x 4,7 k Ω / 2 x 5,6 k Ω)
- lighting feature implemented with white LEDs
- remote lighting control or motion activated lighting capability
- LED indicator
- selectable color of the LED indicator (7 colors available)
- LED indicator remote enable/disable
- remote switching between two levels of PIR sensor sensitivity
- configuration mode remote enable/disable
- supervision of motion detection and supply voltage circuit
- tamper protection against opening of enclosure and removal from mounting
- adjustable mounting holder (**BRACKET D**) included



Alarm signaling time	2
Relay contact resistance (tamper output)	26
Permissible installation height	do 4
Relay contact resistance (alarm output)	26
Tamper outputs (NC relay, resistive load)	40 mA / 24 V DC
Alarm outputs (NC relay, resistive load)	40 mA / 24 V DC
Detection area	20 m x 24 m, 90° (montaż na 2,4 m)
Security grade according to EN50131-2-2	Grade 2
Warm-up period	30
EOL resistors	2 x 1.1 k Ω / 2 x 4.7 k Ω / 2 x 5.6 k Ω
Complied with standards	EN 50131-1, EN 50131-2-2, EN 50130-4, EN 50130-5
Supply voltage	12
Environmental class according to EN50130-5	II
Dimensions	62 x 137 x 42
Maximum humidity	93 \pm 3%
Weight	142
Max. current consumption	97
Standby mode current consumption	13
Recommended mounting height	2.4
Operating temperature range	-10°C...+55°C
Detected target velocity	0.3...3